

NOMA[®] BEAM

Filling mastic



Base	Synthetic dispersion
Consistency	Paste
Density	1,8 g/ml
Time open *	15 minutes
Installation temperatures	+5 °C - +30 °C
Drying time	Approx. 24 hours
Temperature resistance	-20°C bis +70°C
Hardening method	Air humidity

* may vary depending on external factors (such as temperature, humidity and surface type)

Product Description:

The filling mastic for beams is mastic ready for use for sealing between beams and masonry or plastering, as well as for filling small holes or cracks.

Characteristics:

- Free of solvents
- May be sanded when hardened
- Water resistant
- Non-flammable

Packaging:

Colour: white

Content: 310 ml cartridge



NMC sa reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC NMC sa information service. Any partial reproduction or reprint shall require our explicit approval.

NMC sa
Gert-Noël-Straße - B-4731 Eynatten - Belgien
Tel.: +32 87 85 85 00
Fax: +32 87 85 85 11
E-Mail: info@NMC.eu

www.nmc.eu



NOMA[®] BEAM

Filling mastic

**Storage:**

12 months in original unopened packaging in a cool and dry place, at temperatures between 5°C and 25°C.

Substrate:

The substrate must be clean, dry, and free of dust and grease stains. In case of very absorbent substrates, first apply a primer or fixation product.

Application:

Apply the filler and then level with a spatula.

Safety instructions:

Please follow the usual Occupational Health & Safety procedures.