

NOMA[®] BEAM Fixation adhesive



Base	Acrylate
Consistency	Paste
Density	Approx. 1,3 g/ml (DIN 53479)
Polymerisation	Physical polymerisation
Time open	15 minutes
Installation temperature	+5°C - +35°C
Drying time	24 – 48 hours
Temperature resistance	-20°C bis +70°C

Product Description:

The fixation adhesive for beams is a very strong universal adhesive with an extremely high initial adherence (> 140 kg/m²).

Characteristics:

- Free of solvents
- May be painted with water-based paint
- Water resistant
- Initial adherence: 140 kg/m²

Packaging:

Colour: white

Packing: 310 ml cartridges

Storage:

12 months original in unopened packaging in a cool and dry place, at temperatures between 5°C and 25°C.



NMC sa reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC NMC sa information service. Any partial reproduction or reprint shall require our explicit approval.

NMC sa
Gert-Noël-Straße - B-4731 Eynatten - Belgien
Tel.: +32 87 85 85 00
Fax: +32 87 85 85 11
E-Mail: info@NMC.eu

www.nmc.eu



NOMA® BEAMS

Fixation adhesive

**Substrate:**

The substrate must be clean, dry, and free of dust and grease stains.

Types of surfaces:

Painted ceilings, wood substrates, cement, brick or metal. For painted ceilings, scratch the paint in the fixation area (using sandpaper, for example).

Application:

Apply the adhesive to the beam and then press the beam firmly against the ceiling. Quickly remove all excess glue and clean the tools with a moist sponge.

Safety instructions:

Please follow the usual Occupational Health & Safety procedures.