

DOMOSTYL®

Columns for outside use



Constituent material	Polyester resin laminate reinforced with glass fibre. 100% CFC free
Fire classification	B2 according to DIN standard 4102 -1
Resistance to thermal variations	-40°C / +80°C
Thermal and hygrometric expansion	0.1 mm/m/10°C
Tensile strength: Breaking stress Flexing until break	according to ISO standard 1926 41N/mm ² 11%
Shore D	87,9

Name of the product:
DOMOSTYL® columns

Factory finish:
White acrylic primer

Visible surfaces:
The surfaces are painted with a white acrylic primer. The manufacturing technique guarantees a hard and smooth surface.

Installation and storage conditions:
Flat, sheltered from the sun and moisture. Handle with care. Suitable for outside use, solely for decoration.

Tools and adhesive:
Circular saw, jigsaw, drill with wood augers, and right-angle grinder with disc suitable for cutting stone. DOMOSTYL® glue.



NMC sa se réserve le droit de modifier à tout moment et sans avis préalable les caractéristiques et la gamme de ses produits. Les informations contenues dans ce prospectus sont données sur base de bonne foi et en rapport avec les connaissances techniques actuelles. L'application correcte incombe à l'utilisateur. Si ce dernier hésite quant à l'application requise, NMC sa l'invite à s'informer auprès de la société ou de ses représentants.

NMC sa
Gert-Noël-Straße - B-4731 Eynatten - Belgium
Tel.: +32 87 85 85 00
Fax: +32 87 85 85 11
E-Mail: info@nmc.eu

www.nmc.eu



DOMOSTYL®

Columns for outside use

**Installation:**

The installation instructions must be followed.

Surface work:

The DOMOSTYL® columns must be painted. For best results use water-based paints. If you intend to use oil or other solvent based paints, it is advisable to test a small area first. Silicate, silicone and limestonebased paints as well as their derivatives cannot be used in any circumstances.

Important note:

The elements are strictly decorative and do not fulfil any static function. They are thus not designed to support loads or movements. They are not suitable for use as framing for concrete.