

DOMOSTYL® EPS Adhesive



| | |
|----------------------------|---|
| Constituent material | Acrylic coating in paste |
| Dry extract | 77 ± 2% |
| Density | 1.50 ± 0.10 |
| pH | 9.0 ± 0.5 |
| Ignition point | Not applicable |
| Drying | 24h |
| Conditions for application | With ambient temperature and temperature of support higher than 5° (precautions must be taken if the temperature exceeds 25°) |
| AFNOR Classification | T36-005: Family II, class 2b |

Name of the product:
DOMOSTYL® EPS adhesive

Colour:
Light grey

Presentation:
Flexible paste to add to 30% by weight of grey cement when ready for use

Essential characteristics:

- Excellent bonding
- Permeable to water vapour
- Very good plasticity and pliability of use
- Quick drying, hardening and priming



NMC sa reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC NMC sa information service. Any partial reproduction or reprint shall require our explicit approval.

NMC sa
Gert-Noël-Straße - B-4731 Eynatten - Belgien
Tel.: +32 87 85 85 00
Fax: +32 87 85 85 11
E-Mail: info@nmc.eu

www.nmc.eu



