


NOMA® PARKETT SILVER RAPID 3mm



Expanded polystyrene foam, covered with a special vapour-trap film. Ideally suited for laying click system laminate flooring due to the smooth upper surface, as well as cork and floating parquet floors, in areas with normal traffic.

Product features

- Simple and easy to install through zig-zag format
- Reduces walking noise and resonance impact
- For indoor use only




NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

For further information, please contact
the respective subsidiary in your country.
Visit www.nmc.eu/contact

www.nmc.eu



NOMA® PARKETT SILVER RAPID 3mm



- Thickness: 3 mm \pm 0,5 mm
- Impact sound reduction ΔL_w : 20 dB (with laminate) acc. to DIN EN ISO 140-8 / 717-2
- Walking sound improvement: 19% acc. to IHD site norm
- Thermal resistance R at 40°C: \pm 0,09 m²K/W acc. to DIN EN ISO 12667
- Thermal conductivity at 40°C: \pm 0,0329 W/mK
- Water permeability value (Sd value): > 100 m acc. to DIN 52615 / DIN EN 12086
- Compression strength: \pm 5,7 t/m² acc. to ISO 844 (0,5 mm)
- Leveling of floor irregularities: \leq 1,8 mm
- Density: 19 kg/m³ \pm 3 kg
- Surface mass (approx. values): \pm 57 g/m²
- Application temperature range: -40 °C to +70 °C
- Fire classification: E/Efl according to DIN EN 13501-1
- Compatibility with underfloor heating (warm water system): yes
- Laminate up to 9 mm. Take producer information into account.

Installation tips :

The floor must be clean, dry and even. Place a first strip (silver side upwards) and cut it to the size required using a cutter. Unfold the overlapping edge and lay it edge-to-edge against the first. To guarantee a good result, it is essential to attach the layers to each other, using NOMA® PARKETT ADHESIVE & FIX (adhesive tape covered with aluminium for underlay). Where it meets the wall, stick part of the adhesive tape on to NOMA® PARKETT SILVER RAPID and the other against the adjacent wall. Repeat as necessary and then lay the floor.

Range of products

Type	W m	L m	T mm	Packaging unit
3 mm	1	10	3	24x10 m ² /palet
3 mm	1	10	3	6x10 m ² /ctn