

# NOMA® PARKETT EXPERT BLACK SILVER ROLL 1,5mm



Highly elastic polymer with a special vapour-trap foil. The manufacture of this insulation product is certified according to ISO 9001:2000.

## Product features

- Excellent improving of the walking comfort
- High compression stability
- Excellent thermal resistance for an outstanding compatibility with underfloor heating - top-values
- Excellent impact sound reducing
- Excellent water permeability value for an outstanding moisture-bloking result
- Odour- and rot-free
- For indoor use only
- Simply and quick to fit




NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

For further information, please contact the respective subsidiary in your country. Visit [www.nmc.eu/contact](http://www.nmc.eu/contact)

[www.nmc.eu](http://www.nmc.eu)



# NOMA® PARKETT EXPERT BLACK SILVER ROLL 1,5mm



- Thickness: 1,5 mm ± 0,5 mm
- Impact sound reduction  $\Delta L_w$ : 21 dB (for laminates) according to DIN EN ISO 140-8 / 717-2
- Walking sound improvement: 34 % according to IHD site norm
- Thermal resistance R at 40°C: ± 0,004 m<sup>2</sup>K/W nach DIN EN ISO 12667
- Thermal conductivity: ± 0,37 W/m K
- Water permeability value: > 200 m according to DIN 52615 / DIN EN 12086
- Compression strength: > 50 t/m<sup>2</sup> according to ISO 844 (0,5 mm)
- Leveling of floor irregularities: < 0,5 mm
- Density: ± 1600 kg/m<sup>3</sup>
- Surface mass (approx. values): ± 2400 g/m<sup>2</sup>
- Application temperature range: -40 °C to +70 °C
- Fire classification: E/Efl according to DIN EN 13501-1
- Compatibility with underfloor heating (warm water system): yes

## Installations tips:

- The floor must be clean, dry and flat. Unroll the first strip on the floor (polymer side downwards and silver side upwards) and cut it to the size required using a cutter. Unroll on the floor and cut the second strip, which you lay edge-to-edge against the first.
- To guarantee a good result, it is essential to attach the layers to each other, using NOMA®PARKETT ADHESIVE & FIX (adhesive tape covered with aluminium for underlay). Where it meets the wall, stick part of the adhesive tape on the NOMA®PARKETT EXPERT BLACK SILVER ROLL and the other against the adjacent wall. Repeat steps and then fit the floor.

## Range of products

Type	W m	L m	T mm	Packaging unit	Details
1,5 mm	0,75	7,4	1,5	54x5,55 m <sup>2</sup> /palet	0,75x7,4 m= 5,55 m <sup>2</sup> /Roll