


NOMA® PARKETT EXPERT UNIVERSAL ROLL 0,12mm



Multilayer special film manufactured from high-quality raw materials. NOMA® PARKETT EXPERT UNIVERSAL ROLL suited for laying click system laminate flooring as well as floating parquet floors, especially if there is still humidity in the floor. The 3-layer film offers outstanding protection against rising humidity.

Product features

- Protects against rising damp
- High resistance to water vapour diffusion
- High water vapour blocking action
- High safety
- High tensile strength
- Manufactured from high-quality raw materials
- Odour- and rot-free
- Recyclable




NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

For further information, please contact
the respective subsidiary in your country.
Visit www.nmc.eu/contact

www.nmc.eu



NOMA® PARKETT EXPERT UNIVERSAL ROLL 0,12mm



- Thickness (nominal): $\pm 120 \mu\text{m}$ according to DIN EN 2286-3
- Water permeability value (Sd value): $\geq 150 \text{ m}$
- Density: $\pm 830 \text{ kg/m}^3$ according to DIN EN ISO 845
- Surface mass: $\pm 100 \text{ g/m}^2$
- Application temperature range: -40 C° to $+70 \text{ C}^\circ$
- Fire classification: B2 according to DIN 4102

Installation tips:

- Lay out the sheet and pull die edges 15cm upwards the wall.
- Overlap the joints and fix them with water vapour resistant tape (NOMA® PARKETT ADHESIVE & FIX).
- Lay the floor and cut overlapping sheet next to the wall

Range of products

Type	W	L	T	Packaging unit	details
	m	m	mm		
0,12 mm	2	50	0,12	40x100 m ² /ctn	50x2m, folded 50x1m