

NOMA® PARKETT SILVER ROLL 3mm



Expanded polystyrene foam, covered with a special vapour-trap film. Ideally suited for laying click system laminate flooring due to the smooth upper surface, as well as cork and floating parquet floors, in areas with normal traffic.

Product features

- Reduces the impact sound and improves the walking comfort
- Protects against rising damp
- Odour- and rot-free
- For indoor use only
- Simply and quick to fit




NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

For further information, please contact the respective subsidiary in your country. Visit www.nmc.eu/contact

www.nmc.eu



NOMA® PARKETT SILVER ROLL 3mm



- Thickness: 3 mm \pm 0,5 mm
- Impact sound reduction ΔL_w : 20 dB (with laminates) according to DIN EN ISO 140-8 / 717-2
- Walking sound improvement: 19% according to LHD site norm
- Thermal resistance R at 40°C: \pm 0,09 m²K/W according to DIN EN ISO 12667
- Thermal conductivity at 40°C: \pm 0,0329 W/mK
- Water permeability value (Sd value): > 100 m according to DIN 52615 / DIN EN 12086
- Compression strength: \pm 5,7 t/m² according to ISO 844 (0,5 mm)
- Leveling of floor irregularities: \leq 1,8 mm
- Density: 19 kg/m³ \pm 3 kg
- Surface mass (approx. values): \pm 57 g/m²
- Application temperature range: -40 °C to +70 °C
- Fire classification: E/Efl according to DIN EN 13501-1
- Compatibility with underfloor heating (warm water system): yes
- Laminate up to 9mm. Take producer information into account.

Installation tips:

The floor must be clean, dry and flat. Unroll the first length of NOMA®PARKETT SILVER ROLL on the floor and cut it to the size required using a cutter. Unroll on the floor and cut the second length, which you lay edge-to-edge against the first. To guarantee a good result, it is essential to attach the layers to each other, using NOMA®PARKETT ADHESIVE & FIX (adhesive tape covered with aluminium for underlay). Where it meets the wall, stick part of the adhesive tape on the NOMA®PARKETT SILVER ROLL and the other against the adjacent wall. Repeat steps and then fit the floor.

Range of products

Type	W m	L m	T mm	Packaging unit
3 mm	1	10	3	24x10 m ² /palet
3 mm	1	10	3	8x10 m ² /ctn